

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
Relee miniatura									
RM83	1NO; 1C/O; 1NC; 16A	under 100VDC	100	1.43	200	1.33	200	1.33	100
		110VDC sensitive	100	2.62	200	2.44	200	2.44	100
		110VDC	100	1.99	200	1.86	200	1.86	100
RM92	1NO; 1C/O; 1NC; 8A	All voltage	100	1.21	200	1.13	200	1.13	100
RM93	1NO; 1C/O; 1NC; 8A	All voltage	100	1.32	200	1.23	200	1.23	100
RM94	2NO; 2C/O; 2NC; 8A	All voltage	100	1.41	200	1.31	200	1.31	100
RM96	1NO; 1C/O; 1NC; 8A	All voltage	100	1.30	200	1.21	200	1.21	100
RM84	2NO; 2C/O 8A	under 048VDC	100	1.58	200	1.47	200	1.47	100
		048VDC	100	1.69	200	1.58	200	1.58	100
		110VDC	100	1.93	200	1.80	200	1.80	100
		under 048VAC	100	2.06	200	1.92	200	1.92	100
		120VAC	100	2.29	200	2.14	200	2.14	100
		230VAC	100	3.07	200	2.87	200	2.87	100
RM85	1NO; 1C/O 16A	Au 5µm	100	0.43	200	0.40	200	0.40	100
		under 048VDC	100	1.56	200	1.45	200	1.45	100
		048VDC	100	1.67	200	1.55	200	1.55	100
		110VDC	100	1.84	200	1.72	200	1.72	100
		under 048VAC	100	1.99	200	1.86	200	1.86	100
		120VAC	100	2.23	200	2.08	200	2.08	100
RM87	1NO; 1C/O 12A	230VAC	100	3.01	200	2.81	200	2.81	100
		Au 5µm	100	0.22	200	0.20	200	0.20	100
		under 048VDC	100	1.56	200	1.45	200	1.45	100
		048VDC	100	1.67	200	1.55	200	1.55	100
		110VDC	100	1.84	200	1.72	200	1.72	100
		under 048VAC	100	1.99	200	1.86	200	1.86	100
Socli pentru rele									
GW92	PCB; RM87N; RM92		10	0.54	20	0.50	20	0.50	10
GZT92	35mm DIN rail mount; RM87N; RM92		10	1.80	20	1.68	20	1.68	10
GW96	PCB; RM96 1C/O; RM960 1C/O;		10	0.54	20	0.50	20	0.50	10
PW80	PCB; RM84; RM85; RM87L; RM87P		10	0.50	20	0.46	20	0.46	10
GZT80	35mm DIN rail mount; RM84; RM85; RM87L; RM87P		10	1.84	20	1.72	20	1.72	10
retractor clips GZT80-0040			10	0.15	20	0.14	20	0.14	10
Relee miniatura industriale									
		up to 060VDC- 127VAC	10	2.83	20	2.65	20	2.65	10

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM	
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3		
R2-WT	2C/O	12A	110/120VDC and 220/240VAC	10	3.51	20	3.27	20	3.27	10
			220VDC	10	4.13	20	3.86	20	3.86	10
			Light indicator (L)	10	0.52	20	0.48	20	0.48	10
			Diode (D)	10	0.15	20	0.14	20	0.14	10
			0,2 µm Au	10	0.22	20	0.20	20	0.20	10
			5 µm Au	10	1.41	20	1.31	20	1.31	10
R2M	2C/O	5A	up to 060VDC- 127VAC	10	3.38	20	3.15	20	3.15	10
			110/120VDC and 220/240VAC	10	3.72	20	3.47	20	3.47	10
			0,2 µm Au	10	0.22	20	0.20	20	0.20	10
RY2	2C/O	12A	5 µm Au	10	2.77	20	2.58	20	2.58	10
			110/120VDC and 220/240VAC	10	4.13	20	3.86	20	3.86	10
			220VDC	10	4.13	20	3.86	20	3.86	10
Socuri pentru rele										
SU4/2D;	PCB; R2		10	0.58	20	0.55	20	0.55	10	
SU4/2L; G4/2	For PCB; R2		10	0.58	20	0.55	20	0.55	10	
GZT2;	35mm DIN rail mount; R2		10	1.86	20	1.74	20	1.74	10	
GZM2	35mm DIN rail mount; R3		10	2.06	20	1.92	20	1.92	10	
CLIP GZT4-0040			10	0.15	20	0.14	20	0.14	10	
GZ2	35mm DIN rail mount; R2M		10	3.68	20	3.43	20	3.43	10	
S2M	PCB; R2M		10	0.54	20	0.50	20	0.50	10	
G2M	PCB; R2M		10	0.54	20	0.50	20	0.50	10	
CLIP			10	0.15	20	0.14	20	0.14	10	
GZY2	35mm DIN rail mount; RY2		10	2.99	20	2.79	20	2.79	10	
Relee industriale										
R3-WT	3C/O	10A	up to 060VDC-127VAC	10	2.99	20	2.79	20	2.79	10
			110/120VDC and 220/240VAC	10	3.76	20	3.51	20	3.51	10
			220VDC	10	4.54	20	4.24	20	4.24	10
			Light indicator (L)	10	0.52	20	0.48	20	0.48	10
			Diode (D)	10	0.15	20	0.14	20	0.14	10
			0,2 µm Au	10	0.43	20	0.40	20	0.40	10
			5 µm Au	10	2.81	20	2.63	20	2.63	10
			up to 060VDC- 127VAC	10	3.14	20	2.93	20	2.93	10

Tip	Parametrii		Tensiune bobina	Pret EUR(fara TVA)						CMM
				Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
R4-WT	4C/O	6A	110/120VDC and 220/240VAC	10	3.76	20	3.51	20	3.51	10
			220VDC	10	4.54	20	4.24	20	4.24	10
			Light indicator (L)	10	0.52	20	0.48	20	0.48	10
			Diode (D)	10	0.15	20	0.14	20	0.14	10
			0,2 µm Au	10	2.81	20	2.63	20	2.63	10
			5 µm Au	10	2.81	20	2.63	20	2.63	10
Socluri pentru relee										
GZT3	for R3			10	1.99	20	1.86	20	1.86	10
CLIP GZT4-0040				10	0.15	20	0.14	20	0.14	10
SU4L; SU4D; G4	for R4			10	0.58	20	0.55	20	0.55	10
GZ4				10	2.68	20	2.50	20	2.50	10
GZT4				10	2.06	20	1.92	20	1.92	10
GZM4				10	2.16	20	2.02	20	2.02	10
CLIP GZT4-0040				10	0.15	20	0.14	20	0.14	10
Relee industriale										
R15/2P-WT	2C/O	10A	up to 060VDC- 127VAC	10	3.96	20	3.70	20	3.70	10
			110/120VDC and 220/240VAC	10	4.37	20	4.08	20	4.08	10
			220VDC	10	5.52	20	5.15	20	5.15	10
			Light indicator (L)	10	0.61	20	0.57	20	0.57	10
			Diode (D)	10	0.22	20	0.20	20	0.20	10
			0,2 µm Au	10	0.22	20	0.20	20	0.20	10
			5 µm Au	10	1.90	20	1.78	20	1.78	10
			tropical	10	1.95	20	1.82	20	1.82	10
R15/3P-WT	3C/O	10A	up to 060VDC- 127VAC	10	4.37	20	4.08	20	4.08	10
			110/120VDC and 220/240VAC	10	4.85	20	4.52	20	4.52	10
			220VDC	10	6.08	20	5.67	20	5.67	10
			Light indicator (L)	10	0.61	20	0.57	20	0.57	10
			Diode (D)	10	0.22	20	0.20	20	0.20	10
			0,2 µm Au	10	0.32	20	0.30	20	0.30	10
			5 µm Au	10	2.27	20	2.12	20	2.12	10
			tropical	10	1.95	20	1.82	20	1.82	10
			up to 060VDC- 127VAC	10	5.95	20	5.55	20	5.55	10

Tip	Parametrii		Tensiune bobina	Pret EUR(fara TVA)						CMM
				Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
R15/4P	4C/O	10A	110/120VDC and 220/240VAC	10	6.38	20	5.96	20	5.96	10
			220VDC	10	7.27	20	6.79	20	6.79	10
			Light indicator (L)	10	0.61	20	0.57	20	0.57	10
			Diode (D)	10	0.22	20	0.20	20	0.20	10
			0,2 µm Au	10	0.43	20	0.40	20	0.40	10
			5 µm Au tropical	10	2.66	20	2.48	20	2.48	10
RUC/2P	2C/O; 2NO	16A	up to 220VDC	1	5.41	2	5.05	2	5.05	1
			up to 380VAC	1	5.95	2	5.55	2	5.55	1
RUC/3P	3C/O; 3NO	16A	up to 220VDC	1	6.10	2	5.69	2	5.69	1
			up to 380VAC	1	6.75	2	6.30	2	6.30	1
Socluri pentru relee										
PZ8	for R15/2P-WT			10	2.27	20	2.12	20	2.12	10
GZ8			10	2.29	20	2.14	20	2.14	10	
GZU8			10	2.40	20	2.24	20	2.24	10	
GOP8			10	0.39	20	0.36	20	0.36	10	
PZ11/PS11	for R15/3P-WT			10	2.70	20	2.52	20	2.52	10
GZ11			10	2.64	20	2.46	20	2.46	10	
GZU11			10	2.83	20	2.65	20	2.65	10	
GOP11			10	0.50	20	0.46	20	0.46	10	
GZ14	for R15/4P-WT			10	3.05	20	2.85	20	2.85	10
GZ14U			10	4.09	20	3.82	20	3.82	10	
GOP14			10	0.67	20	0.63	20	0.63	10	
GUC11	for GUC			10	5.50	20	5.13	20	5.13	10
Relee de putere										
R20	1NO	30A	up to 024VDC	1	2.92	2	2.73	2	2.73	1
			110VDC	1	3.22	2	3.01	2	3.01	1
			024VAC	1	1.93	2	1.80	2	1.80	1
			048VAC	1	4.15	2	3.88	2	3.88	1
			115VAC	1	4.09	2	3.82	2	3.82	1
R20	2NO	25A	230VAC	1	4.52	2	4.22	2	4.22	1
			up to 024VDC	1	3.53	2	3.29	2	3.29	1
			110VDC	1	3.83	2	3.57	2	3.57	1
			024VAC	1	4.67	2	4.36	2	4.36	1
			048VAC	1	4.74	2	4.42	2	4.42	1
			115VAC	1	4.67	2	4.36	2	4.36	1
			230VAC	1	5.11	2	4.77	2	4.77	1

Tip	Parametrii		Tensiune bobina	Pret EUR(fara TVA)						CMM
				Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
RG25	2NO	25A	all voltage	1	6.92	2	6.46	2	6.46	1
RA2			all voltage (with cover)	1	1.19	2	1.11	2	1.11	1
			all voltage (without cover)	1	1.25	2	1.17	2	1.17	1
Relee de timp										
T-R4E	4C/O	6A	012VDC	1	16.77	2	15.65	2	15.65	1
			024VDC	1	16.98	2	15.85	2	15.85	1
			024VAC	1	16.77	2	15.65	2	15.65	1
			115VAC	1	17.09	2	15.95	2	15.95	1
			230VAC	1	16.44	2	15.35	2	15.35	1
T-R4Wu	4C/O	6A	012VDC	1	16.55	2	15.45	2	15.45	1
			024VDC	1	16.98	2	15.85	2	15.85	1
			024VAC	1	17.31	2	16.16	2	16.16	1
			115VAC	1	16.98	2	15.85	2	15.85	1
			230VAC	1	16.98	2	15.85	2	15.85	1
T-R4Bi	4C/O	6A	012VDC	1	16.44	2	15.35	2	15.35	1
			024VDC	1	16.98	2	15.85	2	15.85	1
			024VAC	1	16.77	2	15.65	2	15.65	1
			115VAC	1	16.88	2	15.75	2	15.75	1
			230VAC	1	17.09	2	15.95	2	15.95	1
T-R4Bp	4C/O	6A	012VDC	1	16.44	2	15.35	2	15.35	1
			024VDC	1	16.98	2	15.85	2	15.85	1
			024VAC	1	16.55	2	15.45	2	15.45	1
			115VAC	1	17.42	2	16.26	2	16.26	1
			230VAC	1	17.09	2	15.95	2	15.95	1
Relee de interfata										
PI6-1P	1C/O	6A	012VDC	10	8.44	20	7.88	20	7.88	10
			024VDC	10	8.44	20	7.88	20	7.88	10
			024VAC/DC	10	9.33	20	8.70	20	8.70	10
			230VAC	10	9.87	20	9.21	20	9.21	10
			230VAC/DC	10	11.38	20	10.62	20	10.62	10
PI6-1T	1C/O	6A	5/32VDC	10	9.87	20	9.21	20	9.21	10
			024VAC/DC	10	10.97	20	10.24	20	10.24	10
			230VAC/DC	10	11.23	20	10.48	20	10.48	10
PI6-OC	1C/O	6A	5/32VDC	10	8.94	20	8.34	20	8.34	10
			024VAC/DC	10	10.08	20	9.41	20	9.41	10
			230VAC/DC	10	10.34	20	9.65	20	9.65	10
			012VDC	10	6.49	20	6.06	20	6.06	10
			024VDC	10	6.49	20	6.06	20	6.06	10
			024VAC/DC	10	6.82	20	6.36	20	6.36	10

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
PIR6W-1P	1C/O 6A	036VDC	10	6.82	20	6.36	20	6.36	10
		042VAC/DC	10	6.82	20	6.36	20	6.36	10
		115VAC/DC	10	7.57	20	7.07	20	7.07	10
		230VAC/DC	10	9.37	20	8.74	20	8.74	10
		3µm Au	10	0.28	20	0.26	20	0.26	10
TR-EM1P-UNI multifunction time relay (7 time function)	1 C/O 8A	12-240 VAC/DC	1	39.07	2	36.46	2	36.46	1
TR4N (multifunction time relay) 10 time function	4C/O 6A	012VDC	1	25.64	2	23.93	2	23.93	1
		024VDC	1	0.00	2	0.00	2	0.00	1
		024VAC	1	0.00	2	0.00	2	0.00	1
		115VAC	1	0.00	2	0.00	2	0.00	1
		230VAC	1	26.50	2	24.73	2	24.73	1
	2C/O 8A	12AC/DC	1	25.53	2	23.83	2	23.83	1
		24AC/DC	1	0.00	2	0.00	2	0.00	1
		115AC	1	0.00	2	0.00	2	0.00	1
		230AC	1	0.00	2	0.00	2	0.00	1
	1C/O 16A	12AC/DC	1	25.53	2	23.83	2	23.83	1
		24AC/DC	1	0.00	2	0.00	2	0.00	1
		115AC	1	0.00	2	0.00	2	0.00	1
		230AC	1	0.00	2	0.00	2	0.00	1
TR-EI1P-UNI asymmetric flasher	1 C/O 8A	12-240 VAC/DC	1	45.03	2	42.03	2	42.03	1
MR-EU3M1P monitoring relay	1 C/O 5A		1	46.96	2	43.83	2	43.83	1
Module tip M									
M21P			20	0.70	40	0.65	40	0.65	20
M21N			20	0.70	40	0.65	40	0.65	20
M31R			20	1.20	40	1.12	40	1.12	20
M31G			20	1.20	40	1.12	40	1.12	20
M32R			20	1.20	40	1.12	40	1.12	20
M32G			20	1.20	40	1.12	40	1.12	20
M33R			20	1.24	40	1.16	40	1.16	20
M33G			20	1.24	40	1.16	40	1.16	20
M41R			20	1.20	40	1.12	40	1.12	20
M41G			20	1.20	40	1.12	40	1.12	20
M42R			20	1.20	40	1.12	40	1.12	20
M42G			20	1.20	40	1.12	40	1.12	20
M43R			20	1.24	40	1.16	40	1.16	20
M43G			20	1.24	40	1.16	40	1.16	20
M51			20	1.18	40	1.10	40	1.10	20
M52			20	1.18	40	1.10	40	1.10	20

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
M53			20	1.18	40	1.10	40	1.10	20
M61R			20	1.20	40	1.12	40	1.12	20
M61G			20	1.20	40	1.12	40	1.12	20
M62R			20	1.20	40	1.12	40	1.12	20
M62G			20	1.20	40	1.12	40	1.12	20
M63R			20	1.26	40	1.18	40	1.18	20
M63G			20	1.26	40	1.18	40	1.18	20
M71			20	1.24	40	1.16	40	1.16	20
M72			20	1.16	40	1.08	40	1.08	20
M73			20	1.16	40	1.08	40	1.08	20
M103			20	1.04	40	0.97	40	0.97	20
M91R			20	1.40	40	1.31	40	1.31	20
M91G			20	1.40	40	1.31	40	1.31	20
M92R			20	1.32	40	1.23	40	1.23	20
M92G			20	1.32	40	1.23	40	1.23	20
M93R			20	1.36	40	1.27	40	1.27	20
M93G			20	1.36	40	1.27	40	1.27	20
Relee subminiatura de semnal									
RSM954-0111-85-1003			100	0.70	200	0.65	200	0.65	100
RSM954-0111-85-1005			100	0.70	200	0.65	200	0.65	100
RSM954-0111-85-1006			100	0.70	200	0.65	200	0.65	100
RSM954-0111-85-1009			100	0.70	200	0.65	200	0.65	100
RSM954-0111-85-1012			100	0.70	200	0.65	200	0.65	100
RSM954-0111-85-1024			100	0.70	200	0.65	200	0.65	100
RM50-3011-85-1003			100	0.62	200	0.58	200	0.58	100
RM50-3011-85-1005			100	0.62	200	0.58	200	0.58	100
RM50-3011-85-1006			100	0.62	200	0.58	200	0.58	100
RM50-3011-85-1009			100	0.62	200	0.58	200	0.58	100
RM50-3011-85-1012			100	0.65	200	0.61	200	0.61	100
RM50-3011-85-1018			100	0.65	200	0.61	200	0.61	100
RM50-3011-85-1024			100	0.65	200	0.61	200	0.61	100
RM50-3011-85-1048			100	0.68	200	0.64	200	0.64	100
RM50-3021-85-1003			100	0.52	200	0.49	200	0.49	100
RM50-3021-85-1005			100	0.52	200	0.49	200	0.49	100
RM50-3021-85-1006			100	0.56	200	0.52	200	0.52	100
RM50-3021-85-1009			100	0.56	200	0.52	200	0.52	100
RM50-3021-85-1012			100	0.56	200	0.52	200	0.52	100
RM50-3021-85-1018			100	0.56	200	0.52	200	0.52	100
RM50-3021-85-1024			100	0.56	200	0.52	200	0.52	100

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
RM50-3021-85-1048			100	0.59	200	0.55	200	0.55	100
RM40-3021-85-1003			100	0.89	200	0.83	200	0.83	100
RM40-3021-85-1005			100	0.89	200	0.83	200	0.83	100
RM40-3021-85-1006			100	0.89	200	0.83	200	0.83	100
RM40-3021-85-1009			100	0.95	200	0.89	200	0.89	100
RM40-3021-85-1012			100	0.95	200	0.89	200	0.89	100
RM40-3021-85-1024			100	0.99	200	0.92	200	0.92	100
RM40-3021-85-1048			100	1.27	200	1.19	200	1.19	100
RM40-2011-85-1003			100	1.05	200	0.98	200	0.98	100
RM40-2011-85-1005			100	1.05	200	0.98	200	0.98	100
RM40-2011-85-1006			100	1.05	200	0.98	200	0.98	100
RM40-2011-85-1009			100	1.18	200	1.10	200	1.10	100
RM40-2011-85-1012			100	1.18	200	1.10	200	1.10	100
RM40-2011-85-1024			100	1.18	200	1.10	200	1.10	100
RM40-2011-85-1048			100	1.46	200	1.37	200	1.37	100
RM40-2211-85-1003			100	1.84	200	1.72	200	1.72	100
RM40-2211-85-1005			100	1.84	200	1.72	200	1.72	100
RM40-2211-85-1006			100	1.84	200	1.72	200	1.72	100
RM40-2211-85-1009			100	1.72	200	1.60	200	1.60	100
RM40-2211-85-1012			100	1.75	200	1.63	200	1.63	100
RM40-2211-85-1024			100	1.75	200	1.63	200	1.63	100
RM40-2211-85-1048			100	2.00	200	1.87	200	1.87	100
RSM850-6112-85-1003			100	1.69	200	1.57	200	1.57	100
RSM850-6112-85-1005			100	1.69	200	1.57	200	1.57	100
RSM850-6112-85-1006			100	1.69	200	1.57	200	1.57	100
RSM850-6112-85-1009			100	1.69	200	1.57	200	1.57	100
RSM850-6112-85-1012			100	1.69	200	1.57	200	1.57	100
RSM850-6112-85-1024			100	1.81	200	1.69	200	1.69	100
RSM850B-6112-85-1003			100	2.00	200	1.87	200	1.87	100
RSM850B-6112-85-1005			100	2.00	200	1.87	200	1.87	100
RSM850B-6112-85-1006			100	2.23	200	2.08	200	2.08	100
RSM850B-6112-85-1009			100	2.23	200	2.08	200	2.08	100
RSM850B-6112-85-1012			100	2.23	200	2.08	200	2.08	100
RSM850B-6112-85-1024			100	2.23	200	2.08	200	2.08	100
RSM850-6112-8M-1003			100	2.39	200	2.23	200	2.23	100
RSM850-6112-8M-1005			100	2.39	200	2.23	200	2.23	100
RSM850-6112-8M-1006			100	2.39	200	2.23	200	2.23	100
RSM850-6112-8M-1009			100	2.39	200	2.23	200	2.23	100
RSM850-6112-8M-1012			100	2.39	200	2.23	200	2.23	100

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
RSM850-6112-8M-1024			100	2.51	200	2.34	200	2.34	100
RSM822-6112-85-S024			100	0.95	200	0.89	200	0.89	100
RSM822-6112-85-1048			100	1.27	200	1.19	200	1.19	100
RSM822-6112-85-S003			100	0.92	200	0.86	200	0.86	100
RSM822-6112-85-S005			100	0.92	200	0.86	200	0.86	100
RSM822-6112-85-S006			100	0.92	200	0.86	200	0.86	100
RSM822-6112-85-S009			100	0.92	200	0.86	200	0.86	100
RSM822-6112-85-S012			100	0.92	200	0.86	200	0.86	100
RSM957-0111-85-S003			100	0.67	200	0.62	200	0.62	100
RSM957-0111-85-S005			100	0.67	200	0.62	200	0.62	100
RSM957-0111-85-S006			100	0.67	200	0.62	200	0.62	100
RSM957-0111-85-S009			100	0.67	200	0.62	200	0.62	100
RSM957-0111-85-S012			100	0.67	200	0.62	200	0.62	100
RSM957-0111-85-S024			100	0.76	200	0.71	200	0.71	100
RSM832-6112-85-S003			100	1.34	200	1.25	200	1.25	100
RSM832-6112-85-S005			100	1.34	200	1.25	200	1.25	100
RSM832-6112-85-S006			100	1.34	200	1.25	200	1.25	100
RSM832-6112-85-S009			100	1.34	200	1.25	200	1.25	100
RSM832-6112-85-S012			100	1.34	200	1.25	200	1.25	100
RSM832-6112-85-1024			100	1.43	200	1.34	200	1.34	100
RSM832-6112-85-1048			100	1.81	200	1.69	200	1.69	100
Solid state relays									
RSR20-D32-A0-24-030-0			1	8.53	2	7.97	2	7.97	1
RSR20-D32-A0-24-030-1			1	8.53	2	7.97	2	7.97	1
RSR20-D32-A1-24-030-0			1	8.19	2	7.65	2	7.65	1
RSR20-D32-A1-24-030-1			1	8.19	2	7.65	2	7.65	1
RSR20-D32-D0-06-030-1			1	7.49	2	6.99	2	6.99	1
RSR20-D32-D1-06-030-1			1	7.49	2	6.99	2	6.99	1
RSR20-D32-A0-38-030-0			1	12.46	2	11.63	2	11.63	1
RSR20-D32-A1-38-030-0			1	12.46	2	11.63	2	11.63	1
RSR30-D05-A1-24-020-1			1	7.67	2	7.16	2	7.16	1
RSR30-D12-A1-24-020-1			1	7.83	2	7.31	2	7.31	1
RSR30-D24-A1-24-020-1			1	7.93	2	7.40	2	7.40	1
RSR30-D05-D1-04-025-1			1	7.05	2	6.58	2	6.58	1
RSR30-D12-D1-04-025-1			1	7.23	2	6.75	2	6.75	1
RSR30-D24-D1-04-025-1			1	7.35	2	6.86	2	6.86	1
RSR30-D48-D1-04-025-1			1	7.53	2	7.03	2	7.03	1
RSR30-D05-D1-02-040-1			1	6.45	2	6.02	2	6.02	1
RSR30-D12-D1-02-040-1			1	6.61	2	6.17	2	6.17	1

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
RSR30-D24-D1-02-040-1			1	6.75	2	6.30	2	6.30	1
RSR30-D48-D1-02-040-1			1	6.75	2	6.30	2	6.30	1
RSR30-D05-D1-24-010-1			1	8.27	2	7.72	2	7.72	1
RSR30-D12-D1-24-010-1			1	8.27	2	7.72	2	7.72	1
RSR30-D24-D1-24-010-1			1	8.27	2	7.72	2	7.72	1
RSR30-D48-D1-24-010-1			1	8.27	2	7.72	2	7.72	1
RSR40-D05-A1-24-010-1-0			1	6.61	2	6.17	2	6.17	1
RSR40-D12-A1-24-010-1-0			1	6.61	2	6.17	2	6.17	1
RSR40-D24-A1-24-010-1-0			1	6.61	2	6.17	2	6.17	1
RSR40-D05-D1-02-040-0-P			1	6.09	2	5.68	2	5.68	1
RSR40-D12-D1-02-040-0-P			1	6.09	2	5.68	2	5.68	1
RSR40-D24-D1-02-040-0-P			1	6.09	2	5.68	2	5.68	1
RSR40-D05-D1-02-040-0-N			1	6.09	2	5.68	2	5.68	1
RSR40-D12-D1-02-040-0-N			1	6.09	2	5.68	2	5.68	1
RSR40-D24-D1-02-040-0-N			1	6.09	2	5.68	2	5.68	1
RSR50-D32-A0-24-100-0			1	15.85	2	14.79	2	14.79	1
RSR50-D32-A0-24-100-1			1	15.85	2	14.79	2	14.79	1
RSR50-D32-A1-24-100-0			1	15.69	2	14.64	2	14.64	1
RSR50-D32-A1-24-100-1			1	15.69	2	14.64	2	14.64	1
RSR50-D32-A0-24-250-0			1	22.48	2	20.98	2	20.98	1
RSR50-D32-A0-24-250-1			1	22.48	2	20.98	2	20.98	1
RSR50-D32-A1-24-250-0			1	22.48	2	20.98	2	20.98	1
RSR50-D32-A1-24-250-1			1	22.48	2	20.98	2	20.98	1
RSR50-D32-A0-24-400-0			1	24.38	2	22.76	2	22.76	1
RSR50-D32-A0-24-400-1			1	24.38	2	22.76	2	22.76	1
RSR50-D32-A1-24-400-0			1	24.22	2	22.61	2	22.61	1
RSR50-D32-A1-24-400-1			1	24.22	2	22.61	2	22.61	1
RSR50-D32-A0-48-150-0			1	25.26	2	23.58	2	23.58	1
RSR50-D32-A0-48-150-1			1	25.26	2	23.58	2	23.58	1
RSR50-D32-A1-48-150-0			1	25.26	2	23.58	2	23.58	1
RSR50-D32-A1-48-150-1			1	25.26	2	23.58	2	23.58	1
RSR50-D32-A0-48-250-0			1	29.79	2	27.80	2	27.80	1
RSR50-D32-A0-48-250-1			1	29.79	2	27.80	2	27.80	1
RSR50-D32-A1-48-250-0			1	29.89	2	27.90	2	27.90	1
RSR50-D32-A1-48-250-1			1	29.89	2	27.90	2	27.90	1
RSR50-D32-A0-48-400-0			1	40.24	2	37.56	2	37.56	1
RSR50-D32-A0-48-400-1			1	40.24	2	37.56	2	37.56	1
RSR50-D32-A1-48-400-0			1	40.94	2	38.21	2	38.21	1
RSR50-D32-A1-48-400-1			1	40.94	2	38.21	2	38.21	1

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
RSR50-A28-A0-24-100-0			1	15.50	2	14.47	2	14.47	1
RSR50-A28-A1-24-100-0			1	15.33	2	14.31	2	14.31	1
RSR50-A28-A0-24-250-0			1	20.73	2	19.35	2	19.35	1
RSR50-A28-A1-24-250-0			1	20.56	2	19.19	2	19.19	1
RSR50-A28-A0-24-400-0			1	23.52	2	21.95	2	21.95	1
RSR50-A28-A1-24-400-0			1	23.00	2	21.46	2	21.46	1
RSR60-D32-A0-48-100-0			1	67.24	2	62.76	2	62.76	1
RSR60-D32-A0-48-250-0			1	81.88	2	76.42	2	76.42	1
RSR60-D32-A0-48-400-0			1	107.66	2	100.48	2	100.48	1
RSR60-D32-A1-48-100-0			1	66.90	2	62.44	2	62.44	1
RSR60-D32-A1-48-250-0			1	81.01	2	75.61	2	75.61	1
RSR60-D32-A1-48-400-0			1	107.14	2	100.00	2	100.00	1
Surse de alimentare									
RPS-30-12	85-264VAC, 120-370VDC	12VDC, 2A	1	29.31	2	27.36	2	27.36	1
RPS-30-24	85-264VAC, 120-370VDC	24VDC, 1,5A	1	29.31	2	27.36	2	27.36	1
RPS-120-12	88-132VAC or 176-264VAC, 120-370VDC	12VDC, 10A	1	59.60	2	55.63	2	55.63	1
RPS-120-24	88-132VAC or 176-264VAC, 120-370VDC	24VDC, 5A	1	59.60	2	55.63	2	55.63	1
RPS-45-24			1	37.86	2	35.34	2	35.34	1
RPS-60-24			1	41.57	2	38.80	2	38.80	1
RPS-75-24			1	53.81	2	50.22	2	50.22	1
RPS-240-24			1	107.02	2	99.89	2	99.89	1
RPS-480-24			1	212.48	2	198.32	2	198.32	1
Sigurante automate									
Circuit-breakers up to 25A	RMSI25-0V16	0,1 - 0,16	1	18.40	2	17.17	2	17.17	1
	RMSI25-0V24	0,16 - 0,24	1	18.40	2	17.17	2	17.17	1
	RMSI25-0V4	0,24 - 0,4	1	18.40	2	17.17	2	17.17	1
	RMSI25-0V6	0,4 - 0,6	1	19.51	2	18.21	2	18.21	1
	RMSI25-1	0,6 - 1	1	21.40	2	19.98	2	19.98	1
	RMSI25-1V6	1 - 1,6	1	21.40	2	19.98	2	19.98	1
	RMSI25-2V4	1,6 - 2,4	1	21.40	2	19.98	2	19.98	1
	RMSI25-3V2	2 - 3,2	1	21.40	2	19.98	2	19.98	1
	RMSI25-4	2,4 - 4	1	21.61	2	20.17	2	20.17	1
	RMSI25-5	3,2 - 5	1	21.61	2	20.17	2	20.17	1
	RMSI25-6	4 - 6	1	21.61	2	20.17	2	20.17	1
	RMSI25-8	5 - 8	1	24.74	2	23.09	2	23.09	1

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
	RMSI25-10	6 - 10	1	24.74	2	23.09	2	23.09	1
	RMSI25-16	10 - 16	1	24.74	2	23.09	2	23.09	1
	RMSI25-20	14 - 20	1	26.19	2	24.45	2	24.45	1
	RMSI25-25	18 - 25	1	26.19	2	24.45	2	24.45	1
Circuit-breakers up to 63A	RMSI63-1V6	1 - 1,6	1	43.92	2	40.99	2	40.99	1
	RMSI63-2V4	1,6 - 2,4	1	43.92	2	40.99	2	40.99	1
	RMSI63-4	2,4 - 4	1	43.92	2	40.99	2	40.99	1
	RMSI63-6	4 - 6	1	43.92	2	40.99	2	40.99	1
	RMSI63-10	6 - 10	1	43.92	2	40.99	2	40.99	1
	RMSI63-16	10 - 16	1	43.96	2	41.03	2	41.03	1
	RMSI63-25	16 - 25	1	49.01	2	45.74	2	45.74	1
	RMSI63-32	22 - 32	1	51.65	2	48.20	2	48.20	1
	RMSI63-40	28 - 40	1	59.10	2	55.16	2	55.16	1
	RMSI63-52	38 - 52	1	66.32	2	61.90	2	61.90	1
RMSI63-63	45 - 63	1	66.32	2	61.90	2	61.90	1	
Accesorii									
Auxiliary contacts	RSI-C11		1	2.75	2	2.57	2	2.57	1
Short circuit indicator switch	RSI-S		1	3.72	2	3.48	2	3.48	1
Undervoltage release	RSI-U230	AC 50Hz, 230V	1	7.58	2	7.07	2	7.07	1
	RSI-U240	AC 50Hz, 240V	1	0.00	2	0.00	2	0.00	1
	RSI-U400	AC 50Hz, 400V	1	0.00	2	0.00	2	0.00	1
	RSI-U415	AC 50Hz, 415V	1	0.00	2	0.00	2	0.00	1
	Shunt release	RSI-W024	AC 50Hz 24V, DC 24 -60V	1	10.55	2	9.85	2	9.85
RSI-W230		AC 50Hz 230V	1	7.58	2	7.07	2	7.07	1
RSI-W240		AC 50Hz 240V	1	0.00	2	0.00	2	0.00	1
RSI-W400		AC 50Hz 400V	1	0.00	2	0.00	2	0.00	1
RSI-W415		AC 50Hz 415V	1	0.00	2	0.00	2	0.00	1
RSI-W11		DC 110-240V	1	10.55	2	9.85	2	9.85	1
Remote controlled operating mechanism		RSI-M		1	33.08	2	30.87	2	30.87
Insulated three-phase busbar modular spacing	RSI-L02	for 2 circuit- breakers	1	5.13	2	4.79	2	4.79	1
	RSI-L03	for 23ircuit- breakers	1	7.10	2	6.62	2	6.62	1
	RSI-L04	for 4 circuit- breakers	1	7.65	2	7.14	2	7.14	1
	RSI-L05	for 5 circuit- breakers	1	7.89	2	7.36	2	7.36	1
	RSI-L12	for 2 circuit- breakers with additional features	1	10.00	2	9.34	2	9.34	1
	RSI-L14	for 4 circuit- breakers with additional features	1	14.08	2	13.14	2	13.14	1
three-phase feed in terminal	RSI-L21		1	6.21	2	5.80	2	5.80	1

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
	RSI-L22		1	5.36	2	5.00	2	5.00	1
	RSI-L23		1	13.97	2	13.04	2	13.04	1
Adapter for connection circuit- breaker with minicontactor	RSI-A		1	3.66	2	3.42	2	3.42	1
mini-contactors, 3 pole, 6A									
024VAC	1NO	CRMI05-30-10-A024	1	8.23	2	7.68	2	7.68	1
024VAC	1NC	CRMI05-30-01-A024	1	8.23	2	7.68	2	7.68	1
048VAC	1NO	CRMI05-30-10-A048	1	8.37	2	7.81	2	7.81	1
048VAC	1NC	CRMI05-30-01-A048	1	8.37	2	7.81	2	7.81	1
110VAC	1NO	CRMI05-30-10-A110	1	7.81	2	7.28	2	7.28	1
110VAC	1NC	CRMI05-30-01-A110	1	7.81	2	7.28	2	7.28	1
230VAC	1NO	CRMI05-30-10-A230	1	9.35	2	8.73	2	8.73	1
230VAC	1NC	CRMI05-30-01-A230	1	9.35	2	8.73	2	8.73	1
024VDC	1NO	CRMI05-30-10-D024	1	9.54	2	8.90	2	8.90	1
220VDC	1NO	CRMI05-30-10-D220	1	10.23	2	9.54	2	9.54	1
mini-contactors, 3 pole, 9A									
024VAC	1NO	CRMI09-30-10-A024	1	9.01	2	8.41	2	8.41	1
024VAC	1NC	CRMI09-30-01-A024	1	9.01	2	8.41	2	8.41	1
048VAC	1NO	CRMI09-30-10-A048	1	8.94	2	8.34	2	8.34	1
048VAC	1NC	CRMI09-30-01-A048	1	8.94	2	8.34	2	8.34	1
110VAC	1NO	CRMI09-30-10-A110	1	8.71	2	8.13	2	8.13	1
110VAC	1NC	CRMI09-30-01-A110	1	8.71	2	8.13	2	8.13	1
230VAC	1NO	CRMI09-30-10-A230	1	9.16	2	8.55	2	8.55	1
230VAC	1NC	CRMI09-30-01-A230	1	9.16	2	8.55	2	8.55	1
024VDC	1NO	CRMI09-30-10-D024	1	10.13	2	9.45	2	9.45	1
220VDC	1NO	CRMI09-30-10-D220	1	10.81	2	10.09	2	10.09	1
mini-contactors, 4 pole, 6A									
024VAC		CRMI05-40-00-A024	1	10.30	2	9.61	2	9.61	1
048VAC		CRMI05-40-00-A048	1	10.56	2	9.85	2	9.85	1
110VAC		CRMI05-40-00-A110	1	10.30	2	9.61	2	9.61	1
230VAC		CRMI05-40-00-A230	1	10.30	2	9.61	2	9.61	1
024VDC		CRMI05-40-00-D024	1	10.36	2	9.67	2	9.67	1
220VDC		CRMI05-40-00-D220	1	10.90	2	10.18	2	10.18	1
mini-contactors, 4 pole, 9A									
024VAC		CRMI09-40-00-A024	1	11.22	2	10.47	2	10.47	1
048VAC		CRMI09-40-00-A048	1	11.50	2	10.73	2	10.73	1
110VAC		CRMI09-40-00-A110	1	10.94	2	10.21	2	10.21	1
230VAC		CRMI09-40-00-A230	1	10.85	2	10.13	2	10.13	1
024VDC		CRMI09-40-00-D024	1	10.90	2	10.18	2	10.18	1

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
220VDC		CRMI09-40-00-D220	1	11.68	2	10.90	2	10.90	1
Contactor relays									
24VDC	4NO	CRMI00-40-00-D024	1	9.78	2	9.12	2	9.12	1
24VDC	3NO+1NC	CRMI00-31-00-D024	1	9.78	2	9.12	2	9.12	1
24VDC	2NO+2NC	CRMI00-22-00-D024	1	9.78	2	9.12	2	9.12	1
230VAC	4NO	CRMI00-40-00-A230	1	9.83	2	9.18	2	9.18	1
230VAC	3NO+1NC	CRMI00-31-00-A230	1	9.83	2	9.18	2	9.18	1
230VAC	2NO+2NC	CRMI00-22-00-A230	1	9.83	2	9.18	2	9.18	1
Add-on blocks for contactors CRMI									
auxiliary contact	1NO+1NC	CR110-11	1	3.77	2	3.52	2	3.52	1
auxiliary contact	2NO	CR110-20	1	3.77	2	3.52	2	3.52	1
auxiliary contact	2NC	CR110-02	1	3.77	2	3.52	2	3.52	1
auxiliary contact	4NO	CR110-40	1	5.61	2	5.24	2	5.24	1
auxiliary contact	3NO+1NC	CR110-31	1	5.61	2	5.24	2	5.24	1
auxiliary contact	2NO+2NC	CR110-22	1	5.61	2	5.24	2	5.24	1
auxiliary contact	1NO+3NC	CR110-13	1	5.61	2	5.24	2	5.24	1
auxiliary contact	4NC	CR110-04	1	5.61	2	5.24	2	5.24	1
Contactors, 3 pole, 9A									
24VAC	1NO	CRNI09-30-10-A024	1	10.82	2	10.10	2	10.10	1
24VAC	1NC	CRNI09-30-01-A024	1	10.82	2	10.10	2	10.10	1
110VAC	1NO	CRNI09-30-10-A110	1	10.82	2	10.10	2	10.10	1
110VAC	1NC	CRNI09-30-01-A110	1	10.82	2	10.10	2	10.10	1
230VAC	1NO	CRNI09-30-10-A230	1	10.82	2	10.10	2	10.10	1
230VAC	1NC	CRNI09-30-01-A230	1	10.82	2	10.10	2	10.10	1
400VAC	1NO	CRNI09-30-10-A400	1	10.82	2	10.10	2	10.10	1
400VAC	1NC	CRNI09-30-01-A400	1	10.82	2	10.10	2	10.10	1
24VDC		CRNI09-30-00-D024	1	19.91	2	18.58	2	18.58	1
220VDC		CRNI09-30-00-D220	1	14.54	2	13.57	2	13.57	1
Contactors, 3 pole, 12A									
24VAC	1NO	CRNI12-30-10-A024	1	13.54	2	12.64	2	12.64	1
24VAC	1NC	CRNI12-30-01-A024	1	13.54	2	12.64	2	12.64	1
110VAC	1NO	CRNI12-30-10-A110	1	13.54	2	12.64	2	12.64	1
110VAC	1NC	CRNI12-30-01-A110	1	13.54	2	12.64	2	12.64	1
230VAC	1NO	CRNI12-30-10-A230	1	13.54	2	12.64	2	12.64	1
230VAC	1NC	CRNI12-30-01-A230	1	13.54	2	12.64	2	12.64	1
400VAC	1NO	CRNI12-30-10-A400	1	13.54	2	12.64	2	12.64	1
400VAC	1NC	CRNI12-30-01-A400	1	13.54	2	12.64	2	12.64	1
24VDC		CRNI12-30-00-D024	1	25.31	2	23.63	2	23.63	1
220VDC		CRNI12-30-00-D220	1	17.53	2	16.36	2	16.36	1

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
Contactors, 3 pole, 16A									
024VAC		CRNI16-30-00-A024	1	17.91	2	16.72	2	16.72	1
110VAC		CRNI16-30-00-A110	1	17.91	2	16.72	2	16.72	1
230VAC		CRNI16-30-00-A230	1	17.91	2	16.72	2	16.72	1
400VAC		CRNI16-30-00-A400	1	17.91	2	16.72	2	16.72	1
024VDC		CRNI16-30-00-D024	1	26.48	2	24.72	2	24.72	1
220VDC		CRNI16-30-00-D220	1	19.47	2	18.17	2	18.17	1
24VDC		CRNI12-30-00-D024	1	25.31	2	23.63	2	23.63	1
220VDC		CRNI12-30-00-D220	1	17.53	2	16.36	2	16.36	1
Contactors, 3 pole, 22A									
024VAC		CRNI22-30-00-A024	1	21.42	2	19.99	2	19.99	1
110VAC		CRNI22-30-00-A110	1	21.42	2	19.99	2	19.99	1
230VAC		CRNI22-30-00-A230	1	21.42	2	19.99	2	19.99	1
400VAC		CRNI22-30-00-A400	1	21.42	2	19.99	2	19.99	1
024VDC		CRNI22-30-00-D024	1	37.00	2	34.53	2	34.53	1
220VDC		CRNI22-30-00-D220	1	20.45	2	19.08	2	19.08	1
Contactors, 3 pole, 32A									
024VAC		CRNI32-30-00-A024	1	36.03	2	33.62	2	33.62	1
110VAC		CRNI32-30-00-A110	1	36.03	2	33.62	2	33.62	1
230VAC		CRNI32-30-00-A230	1	36.03	2	33.62	2	33.62	1
400VAC		CRNI32-30-00-A400	1	36.03	2	33.62	2	33.62	1
024VDC		CRNI32-30-00-D024	1	55.50	2	51.80	2	51.80	1
220VDC		CRNI32-30-00-D220	1	33.10	2	30.90	2	30.90	1
Contactors, 3 pole, 38A									
024VAC		CRNI38-30-00-A024	1	37.97	2	35.44	2	35.44	1
110VAC		CRNI38-30-00-A110	1	37.97	2	35.44	2	35.44	1
230VAC		CRNI38-30-00-A230	1	37.97	2	35.44	2	35.44	1
400VAC		CRNI38-30-00-A400	1	37.97	2	35.44	2	35.44	1
024VDC		CRNI38-30-00-D024	1	62.31	2	58.16	2	58.16	1
220VDC		CRNI38-30-00-D220	1	35.05	2	32.71	2	32.71	1
Contactors, 3 pole, 45A									
024VAC	2NO+2NC	CRNI45-30-22-A024	1	51.76	2	48.31	2	48.31	1
110VAC	2NO+2NC	CRNI45-30-22-A110	1	51.76	2	48.31	2	48.31	1
230VAC	2NO+2NC	CRNI45-30-22-A230	1	51.76	2	48.31	2	48.31	1
400VAC	2NO+2NC	CRNI45-30-22-A400	1	51.76	2	48.31	2	48.31	1
024VDC	2NO+2NC	CRNI45-30-22-D024	1	72.70	2	67.85	2	67.85	1
220VDC	2NO+2NC	CRNI45-30-22-D220	1	67.51	2	63.01	2	63.01	1
Contactors, 3 pole, 63A									
024VAC	2NO+2NC	CRNI63-30-22-A024	1	69.13	2	64.52	2	64.52	1

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
110VAC	2NO+2NC	CRNI63-30-22-A110	1	76.81	2	71.69	2	71.69	1
230VAC	2NO+2NC	CRNI63-30-22-A230	1	69.13	2	64.52	2	64.52	1
400VAC	2NO+2NC	CRNI63-30-22-A400	1	76.81	2	71.69	2	71.69	1
024VDC	2NO+2NC	CRNI63-30-22-D024	1	97.37	2	90.87	2	90.87	1
220VDC	2NO+2NC	CRNI63-30-22-D220	1	83.73	2	78.15	2	78.15	1
Contactors, 3 pole, 75A									
024VAC	2NO+2NC	CRNI75-30-22-A024	1	89.25	2	83.30	2	83.30	1
110VAC	2NO+2NC	CRNI75-30-22-A110	1	89.25	2	83.30	2	83.30	1
230VAC	2NO+2NC	CRNI75-30-22-A230	1	89.25	2	83.30	2	83.30	1
400VAC	2NO+2NC	CRNI75-30-22-A400	1	89.25	2	83.30	2	83.30	1
024VDC	2NO+2NC	CRNI75-30-22-D024	1	103.86	2	96.93	2	96.93	1
220VDC	2NO+2NC	CRNI75-30-22-D220	1	61.66	2	57.55	2	57.55	1
Contactors, 3 pole, 85A									
024VAC	2NO+2NC	CRNI85-30-22-A024	1	114.03	2	106.42	2	106.42	1
110VAC	2NO+2NC	CRNI85-30-22-A110	1	114.03	2	106.42	2	106.42	1
230VAC	2NO+2NC	CRNI85-30-22-A230	1	114.03	2	106.42	2	106.42	1
400VAC	2NO+2NC	CRNI85-30-22-A400	1	114.03	2	106.42	2	106.42	1
024VDC	2NO+2NC	CRNI85-30-22-D024	1	128.74	2	120.16	2	120.16	1
220VDC	2NO+2NC	CRNI85-30-22-D220	1	91.96	2	85.83	2	85.83	1
Contactors, 4 pole, 9A									
		CRNI09-40-00-A230	1	20.77	2	19.39	2	19.39	1
		CRNI09-40-00-D024	1	21.64	2	20.19	2	20.19	1
		CRNI09-40-00-D220	1	14.71	2	13.73	2	13.73	1
Contactors, 4 pole, 12A									
230VAC		CRNI12-40-00-A230	1	27.26	2	25.44	2	25.44	1
024VDC		CRNI12-40-00-D024	1	26.29	2	24.54	2	24.54	1
220VDC		CRNI12-40-00-D220	1	18.50	2	17.27	2	17.27	1
Auxiliary contactors									
24VDC	4NO	CRNI00-40-00-D024	1	14.60	2	13.63	2	13.63	1
24VDC	3NO+1NC	CRNI00-31-00-D024	1	14.60	2	13.63	2	13.63	1
24VDC	2NO+2NC	CRNI00-22-00-D024	1	14.60	2	13.63	2	13.63	1
230VAC	4NO	CRNI00-40-00-A230	1	10.91	2	10.18	2	10.18	1
230VAC	3NO+1NC	CRNI00-31-00-A230	1	10.91	2	10.18	2	10.18	1
230VAC	2NO+2NC	CRNI00-22-00-A230	1	10.91	2	10.18	2	10.18	1
Add-on blocks for contactors CRNI									
auxiliary contacts	1NO+1NC	CRI20-11	1	3.21	2	3.00	2	3.00	1
auxiliary contacts	1NO	CRI20-10	1	2.34	2	2.18	2	2.18	1
auxiliary contacts	1NC	CRI20-01	1	2.34	2	2.18	2	2.18	1
Contactors over 100A									

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
230VAC; 115A, 3 pole	2NO+2NC	CRLI110-30-22-A230	1	101.26	2	94.51	2	94.51	1
230VAC; 145A, 3 pole	2NO+2NC	CRLI145-30-22-A230	1	170.50	2	159.13	2	159.13	1
230VAC; 180A, 3 pole	2NO+2NC	CRLI170-30-22-A230	1	188.67	2	176.09	2	176.09	1
230VAC; 210A, 3 pole	2NO+2NC	CRLI210-30-22-A230	1	0.00	2	0.00	2	0.00	1
230VAC; 250A, 3 pole	2NO+2NC	CRLI250-30-22-A230	1	259.64	2	242.33	2	242.33	1
230VAC; 310A, 3 pole	2NO+2NC	CRLI310-30-22-A230	1	311.57	2	290.80	2	290.80	1
230VAC; 400A, 3 pole	2NO+2NC	CRLI400-30-22-A230	1	484.66	2	452.35	2	452.35	1
Adjustment rated range (A)		Ordering codes							
0,1-0,16		RSTM-0V16	1	26.67	2	24.89	2	24.89	1
0,16-0,25		RSTM0V25	1	26.67	2	24.89	2	24.89	1
0,25-0,4		RSTM-0V4	1	26.67	2	24.89	2	24.89	1
0,4-0,63		RSTM-0V63	1	26.67	2	24.89	2	24.89	1
0,63-1		RSTM-1	1	26.67	2	24.89	2	24.89	1
0,8-1,25		RSTM-1V25	1	26.67	2	24.89	2	24.89	1
1-1,6		RSTM-1V6	1	26.67	2	24.89	2	24.89	1
1,25-2		RSTM-2	1	26.67	2	24.89	2	24.89	1
1,6-2,5		RSTM-2V5	1	26.67	2	24.89	2	24.89	1
2-3,2		RSTM-3V2	1	26.67	2	24.89	2	24.89	1
2,5-4		RSTM-4	1	26.67	2	24.89	2	24.89	1
3,2-5		RSTM-5	1	26.67	2	24.89	2	24.89	1
4-6,3		RSTM-6V3	1	26.67	2	24.89	2	24.89	1
5-8		RSTM-8	1	26.67	2	24.89	2	24.89	1
6,3-10		RSTM-10	1	26.67	2	24.89	2	24.89	1
8-12		RSTM-12	1	26.67	2	24.89	2	24.89	1
		CR-310	1	2.76	2	2.57	2	2.57	1
0,1-0,16		RSTN1-1V6	1	14.73	2	13.75	2	13.75	1
0,16-0,25		RSTN1-0V25	1	14.73	2	13.75	2	13.75	1
0,25-0,4		RSTN1-0V4	1	14.73	2	13.75	2	13.75	1
0,4-0,63		RSTN1-0V63	1	14.73	2	13.75	2	13.75	1
0,63-1		RSTN1-1	1	14.73	2	13.75	2	13.75	1
0,8-1,25		RSTN1-1V25	1	14.73	2	13.75	2	13.75	1
1-1,6		RSTN1-1V6	1	14.73	2	13.75	2	13.75	1
1,25-2		RSTN1-2	1	14.73	2	13.75	2	13.75	1
1,6-2,5		RSTN1-2V5	1	14.73	2	13.75	2	13.75	1
2-3,2		RSTN1-3V2	1	14.73	2	13.75	2	13.75	1
2,5-4		RSTN1-4	1	14.73	2	13.75	2	13.75	1
3,2-5		RSTN1-5	1	14.73	2	13.75	2	13.75	1
4-6,3		RSTN1-6V3	1	14.73	2	13.75	2	13.75	1
5-8		RSTN1-8	1	14.73	2	13.75	2	13.75	1

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
6,3-10		RSTN1-10	1	14.73	2	13.75	2	13.75	1
8-12,5		RSTN1-12V5	1	14.73	2	13.75	2	13.75	1
10-14,5		RSTN1-14V5	1	14.73	2	13.75	2	13.75	1
		CRI-320	1	5.61	2	5.24	2	5.24	1
4-6,3		RSTN2-6V3	1	20.95	2	19.55	2	19.55	1
5-8		RSTN2-8	1	20.95	2	19.55	2	19.55	1
6,3-10		RSTN2-10	1	20.95	2	19.55	2	19.55	1
8-12,5		RSTN2-12V5	1	20.95	2	19.55	2	19.55	1
10-16		RSTN2-16	1	20.95	2	19.55	2	19.55	1
12,5-20		RSTN2-20	1	20.95	2	19.55	2	19.55	1
16-25		RSTN2-25	1	20.95	2	19.55	2	19.55	1
		CRI-330	1	5.89	2	5.49	2	5.49	1
Adjustment rated range (A)									
8-12,5		RSTN3-12V5	1	25.12	2	23.44	2	23.44	1
10-16		RSTN3-16	1	25.12	2	23.44	2	23.44	1
12,5-20		RSTN3-20	1	25.12	2	23.44	2	23.44	1
16-25		RSTN3-25	1	25.12	2	23.44	2	23.44	1
20-32		RSTN3-32	1	25.12	2	23.44	2	23.44	1
25-36		RSTN3-36	1	25.12	2	23.44	2	23.44	1
32-40		RSTN3-40	1	26.14	2	24.40	2	24.40	1
36-45		RSTN3-45	1	26.14	2	24.40	2	24.40	1
		CRI-340	1	8.46	2	7.90	2	7.90	1
12,5-20		RSTN4-20	1	29.46	2	27.50	2	27.50	1
16-25		RSTN4-25	1	29.46	2	27.50	2	27.50	1
20-32		RSTN4-32	1	29.46	2	27.50	2	27.50	1
25-40		RSTN4-36	1	29.46	2	27.50	2	27.50	1
32-50		RSTN4-40	1	29.46	2	27.50	2	27.50	1
40-57		RSTN4-45	1	29.46	2	27.50	2	27.50	1
50-63		RSTN4-63	1	29.46	2	27.50	2	27.50	1
57-70		RSTN4-70	1	38.32	2	35.76	2	35.76	1
63-80		RSTN4-80	1	38.32	2	35.76	2	35.76	1
70-88		RSTN4-88	1	38.32	2	35.76	2	35.76	1
		CRI-350	1	8.01	2	7.48	2	7.48	1
55-80		RSTL1-80	1	44.70	2	41.72	2	41.72	1
63-90		RSTL1-90	1	44.70	2	41.72	2	41.72	1
80-110		RSTL1-110	1	44.70	2	41.72	2	41.72	1
90-120		RSTL1-120	1	44.70	2	41.72	2	41.72	1
110-135		RSTL1-135	1	48.45	2	45.22	2	45.22	1
		CRI-360	1	11.13	2	10.38	2	10.38	1

LISTA DE PRETURI

Tip	Parametrii	Tensiune bobina	Pret EUR(fara TVA)						CMM
			Cant 1	Pret 1	Cant 2	Pret 2	Cant 3	Pret 3	
55-80		RSTL2-80	1	44.70	2	41.72	2	41.72	1
63-90		RSTL2-90	1	44.70	2	41.72	2	41.72	1
80-110		RSTL2-110	1	44.70	2	41.72	2	41.72	1
90-120		RSTL2-120	1	44.70	2	41.72	2	41.72	1
110-135		RSTL2-135	1	48.45	2	45.22	2	45.22	1
120-150		RSTL2-150	1	48.45	2	45.22	2	45.22	1
		CRI-370	1	24.83	2	23.17	2	23.17	1
55-80		RSTL3-80	1	44.70	2	41.72	2	41.72	1
63-90		RSTL3-90	1	44.70	2	41.72	2	41.72	1
80-110		RSTL3-110	1	44.70	2	41.72	2	41.72	1
90-120		RSTL3-120	1	44.70	2	41.72	2	41.72	1
110-135		RSTL3-135	1	48.45	2	45.22	2	45.22	1
120-150		RSTL3-150	1	48.45	2	45.22	2	45.22	1
135-160		RSTL3-160	1	48.45	2	45.22	2	45.22	1
150-180		RSTL3-180	1	48.45	2	45.22	2	45.22	1
		CRI-381	1	24.83	2	23.17	2	23.17	1
		CRI-382	1	28.05	2	26.18	2	26.18	1
80-125		RSTL4-125	1	93.66	2	87.42	2	87.42	1
125-200		RSTL4-200	1	93.66	2	87.42	2	87.42	1
160-250		RSTL4-250	1	98.77	2	92.18	2	92.18	1
200-320		RSTL4-320	1	98.77	2	92.18	2	92.18	1
250-400		RSTL4-400	1	98.77	2	92.18	2	92.18	1
		CRI-390	1	26.67	2	24.89	2	24.89	1